

### Application

Pour traverse, étrier ou poteau.

### Matière


1. Acier galvanisé à chaud
2. Alliage d'aluminium.

### Application

For crossarm, bracket or pole.

### Material

1. Hot dip galvanized steel
2. Aluminium alloy.

Code	Reference	D (mm)	L (mm)	Charge utilisation maxi Max. service load Fx/Fy (daN)	Nbre écrous Quantity nuts	Cond' Packing	 (kg)
P10088868	BQC 12 50	12	50	250/160	2	1	0,180
P077053001	BQC 12 55	12	55	250/160	2	1	0,140
DX54453	BQC 12 CH	12	110	250/160	Cheville/Plug	1	0,265
DX07158	BQC 12 110 2 ECR	12	110	250/160	2	1	0,230
DX02161	BQC 12 200	12	200	250/160	2	1	0,266
P077053002	BQC 12 250	12	250	250/160	2	1	0,260
P077053003	BQC 12 300	12	300	250/160	2	1	0,310
DX02167	BQC 14 250	14	250	480/250	2	1	0,360
P977053007	BQC 14 300	14	300	480/250	2	1	0,420
P10038792	BQC 16 320	16	320	730/330	2	5	0,980

Nota : les caractéristiques techniques sont données à titre indicatif et peuvent être modifiées sans préavis – Photos non contractuelles  
The characteristics are given for information and can be changed without prior notice. Photos for illustration only

FPP9770530XX\_BQC\_202309\_FGB

